

SPECIFICATION OF BASE OIL SN650

GENERAL DESCRIPTION OF BASE OIL SN650

VIRGIN BASE OIL SN 650 IS BASE OIL CATEGORIZED IN GROUP I IS THE COMMON QUALITY BASE OIL PRODUCT OF ATDM WHICH USE IN DIFFERENT APPLICATIONS THIS GRADE SN 650 IS A BASE OIL AT THE UPPER END OF THE SPECIFICATIONS FOR GRADE I BASE OILS. THEY ARE MAINLY USED IN LUBRICANT PRODUCTION. IT IS A GROUP I BASE OIL WHICH HAS UNDERGONE SOLVENT REFINING AND DE-WAXING PROCESSES. TO FINISH THE REFINING IT IS HYDROGEN TREATED TO CLEAR IMPURITIES.

USES OF BASE OIL SN650

Base oil sn650 use in manufacturing of many lubricants oil , who produce base oil mostly use sn650 as industrial burners , mold oil to help release products from their molds , hydraulic oil , bitumen base products , additive in manufactured products like lubricant, transformer oil , industrial burners.

PACKING OF BASE OIL SN650

BASE OIL SN650 PACKED IN NEW OR USED 180 KG DRUMS , ISO TANK , FLEXI TANKS AND BULK SHIPMENTS. EACH 20 FOOT CONTAINER TAKES 80 DRUM .

GUARANTY/WARRANTY OF BASE OIL SN650

ATDM GUARANTY THE QUALITY OF VIRIGN BASE OIL SN650 WITH ARRANGEMENT OF INTERNATIONAL INSPECTOR TO CHECK QUALITY AND QUANTITY OF VIRGIN BASE OIL SN650 DURING THE LOADING TO VESSEL AND CONTROLLING THE PRODUCTION BY QC BY BATCH TEST REPORT BEFORE SHIPPING. ATDM GUARANTY THE QUALITY TO MEET WITH ASTM.

OUR APPROVALS



BASE OIL SN650 ANALISES:

| SPECIFICATION | METHOD | SN650 |
|-----------------|--------------|--------------|
| Viscosity @100 | ASTM D445 | 12-14 |
| Viscosity Index | ASTM D2270 | 85 MIN |
| Flash point | ASTM D92 | 250 |
| Pour point | ASTM D97 | -6 |
| Color | ASTM D1500 | 3 |
| Appearance | Slight/ melt | BRIGHT/CLEAR |