

## **SPECIFICATION OF HIGH VISCOSITY PARAFFINIC RPO**

### **GENERAL DESCRIPTION OF HIGH VISCOSITY PARAFFINIC RPO**

PARAFFINIC RUBBER PROCESS OIL WITH HIGH VISCOSITY INDEX IS A TRANSPARENT BROWN COLOR THIS OIL MAINLY USE IN PLASTIC PRODUCT WHICH ELASTICITY IS IMPORTANT PARAMETER. HIGH VISCOS PRARAFFINIC OIL CONTAIN 45% PARAFFINIC CARBON AND EVAPORATION IS 1% AT 150 ° C .

### **USES OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL**

PARAFFINIC RUBBER PROCESS OIL WITH HIGH VISCOSITY MAINLY USE IN : RUBBER PRODUCTS SUCH AS TUBES WITH HIGH ELASTICITY, SOFT RUBBER COATING, RUBBER GASKETS, RUBBER GASKETS, SEALING RINGS , PLASTIC LAYER USED IN HOME APPLIANCES...

### **PACKING OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL**

PARAFFINIC RUBBER PROCESS OIL WITH HIGH VISCOSITY IS PACKED IN NEW OR USED 180 KG DRUMS , ISO TANK , FLEXI TANKS AND BULK SHIPMENTS. EACH 20 FOOT CONTAINER TAKES 80 DRUM HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL.

### **GUARANTY/WARRANTY OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL**

ATDM GUARANTY THE QUALITY OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL WITH ARRANGEMENT OF INTERNATIONAL INSPECTOR TO CHECK QUALITY AND QUANTITY OFHIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL DURING THE LOADING TO VESSEL AND CONTROLLING THE PRODUCTION BY QC BY BATCH TEST REPORT BEFORE SHIPPING. ATDM GUARANTY THE QUALITY TO MEET WITH ASTM.

### **OUR APPROVALS**



**HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL ANALISES:**

<b>PARAFFINIC RUBBER PROCESS OIL</b>	
<b>Characteristics</b>	<b>TEST RESULT</b>
<b>Kinematic Viscosity @ 100 Deg. C, cST</b>	15-40
<b>AP</b>	120
<b>Kinematic Viscosity @ 40 Deg. C, cST</b>	40
<b>Flash point, Deg. C</b>	170
<b>PCA</b>	3 %
<b>Specific gravity @15 Deg C</b>	0.97