

SPECIFICATION OF EXTRACT

GENERAL DESCRIPTION OF EXTRACT

THIS PRODUCT IS FULLY RICH AROMATIC BY-PRODUCT FROM SOLVENT EXTRACTING PROCESS TO MODIFY PHYSICAL PROPERTIES OF THE VULCANIZATION AND TO REDUCE THE COST OF THE FINISHED PRODUCT. THIS PRODUCT HAS GOOD ELASTOMERIC COMPATIBILITY AND LOW VOLATILITY.

USES OF EXTRACT RUBBER PROCESS OIL

RUBBER PROCESS OIL IS USED IN INDUSTRY INK FORMULATIONS, ISOLATION MANUFACTURERS ,ATOUMOBILE TIRE MAKING FACTORY , RUBBER MANUFACTURING , SHOES , FLOORING , CABLE AND ANY OTHER INDUSTRIAL INTERFACE .

PACKING OF EXTRACT RPO

RUBBER PROCESS OIL IS PACKED IN NEW OR USED 180 KG DRUMS, ISO TANK, FLEXI TANKS AND BULK SHIPMENTS. EACH 20 FOOT CONTAINER TAKES 80 DRUM EXTRACT RUBBER PROCESS OIL.

GUARANTY/WARRANTY OF EXTRACT RUBBER PROCESS OIL

ATDM GUARANTY THE QUALITY OF EXTRACT RUBBER PROCESS OIL WITH ARRANGEMENT OF INTERNATIONAL INSPECTOR TO CHECK QUALITY AND QUANTITY OFEXTRACT RUBBER PROCESS OIL DURING THE LOADING TO VESSEL AND CONTROLLING THE PRODUCTION BY QC BY BATCH TEST REPORT



BEFORE SHIPPING. ATDM GUARANTY THE QUALITY TO MEET WITH ASTM.

OUR APPROVALS









EXTRACT RUBBER PROCESS OIL ANALISES:

Test	Norm	Unit
^{C°} Kinematic Viscosity @100	ASTM D-445	40-70
(min) Flash point	ASTM D-92	235C
Aniline point	ASTM D611- IP-2	27-37