

# SPECIFICATION OF SLACK WAX

## **GENERAL DESCRIPTION OF SLACK WAX**

SLACK WAX IS PETROLEUM PRODUCT, SLACK WAX IS THE RAW MATERIAL OF PARAFFIN WAX, IT IS A MIXTURE OF OIL AND WAX IN YELLOW OR BROWN COLOR, SLACK WAX PROCESSED BY PRESSING TO DECREASE THE OIL CONTENT AND DISCOLORING BY SPECIAL POWDERS AFTER HEATING TO PRODUCE PARAFFIN WAX.

ALL THE TYPES OF SLACK WAX ARE USED AS BLENDING COMPONENTS OR WATERPROOFING AGENTS IN THE MANUFACTURE OF VARIOUS INDUSTRIAL PRODUCTS.

### **USES OF SLACK WAX**

SLACK WAX IS USED IN EMULSIONS, CONSTRUCTION BOARD, MATCHES, CANDLES, RUST PROTECTIVE PRODUCTS AND MOISTURE VAPOR BARRIERS, POLISHES, INKS, CARBON PAPER AND EXTERNALLY CAN BE APPLIED AS GOOD DUST SUPPRESSANTS OR CONTROLLED-RELEASE AGENTS FOR VARIOUS CHEMICAL AND FERTILIZERS.

#### **PACKING OF SLACK WAX**

SLACK WAX IS PACKED IN NEW OR SECOND HAND 180 KG DRUMS, ISO TANK, FLEXI TANKS. EACH 20 FOOT CONTAINER TAKES 110 DRUMMED SLACK WAX.

#### **GUARANTY/WARRANTY OF SLACK WAX**







ATDM GUARANTY THE QUALITY OF SLACK WAX WITH ARRANGEMENT OF INTERNATIONAL INSPECTOR TO CHECK QUALITY AND QUANTITY OF SLACK WAX DURING THE LOADING TO VESSEL AND CONTROLLING THE PRODUCTION BY QC BY BATCH TEST REPORT BEFORE SHIPPING. ATDM GUARANTY THE QUALITY TO MEET WITH ASTM .

#### **OUR APPROVALS**







